



QUICKFLEX REVOLUTION®

THE ONLY WATER-BASED, ECO-FRIENDLY UNIVERSAL HEAT TRANSFER VINYL.

This soft, matte heat transfer vinyl can be applied to all fabrics, including nylon. Water-based and one of the most environmentally friendly HTVs available, it is easy to use and quick to apply.

TECHNICAL DATA	
	COMPOSITION Water based PU
	THICKNESS 90 µm
	CARRIER Transparent adhesive polyester carrier
CUT SETTINGS	
	SIDE Mirror cut
	CUTTING 45° flex blade
APPLICATION	
	TEXTILE Cotton, polyester, polycotton, nylon fabrics
 	TIME & TEMPERATURE Quick application : 140°C/284°F -5s Low temp. : 120°C/248°F - 20s Nylon : 1°: 140°C/284°F - 5s / 2°: 140°C/284°F - 15s
	PRESSURE Medium
	PEEL Cold peel or Hot peel

PRODUCT HIGHLIGHTS		
- Water-based polyurethane (PU). - Smooth and soft to the touch. - Smooth and soft to the touch. - Suitable for all fabric types, including nylon. - Easy to cut, weed and peel, whether hot or cold.		
CARE & MAINTENANCE		
- Always follow the care instructions for the garment. - Wash inside out to extend the design's life. - Wait 24 hours after application for the first wash. - Avoid using of aggressive products. - Do not bleach.		
WASHING	IRONING	TUMBLE-DRY
 60°C / 140°F 40°C / 104°F	 Inside out only	 Allowed
STEP BY STEP : HOW TO USE		
STEP 1 - Perform a test cut using your cutting plotter.		
STEP 2 - Mirror cut the heat transfer vinyl using a 45° flex blade.		
STEP 3 - Weed the excess material and apply the design to the garment.		
STEP 4 - Press and peel the carrier hot or cold.		

NOTE: We strongly recommend carrying out cutting, heat press and application tests before production.

CHEMICA SAS 35 rue de Malacussy , 42000 Saint-Etienne, FRANCE