






NEWJET





MATTE-PRINTABLE HOT TRANSFER FILM DEDICATED TO PERSONALISATION OF LIGHT-COLOURED TEXTILES WITH INKJET PRINTERS

Would you like to personalise your textiles with an inkjet office printer? Newjet is a printable heat transfer film with a matt finish and a soft feel that is fully compatible with office printers. It is dedicated to light-coloured textiles.

TECHNICAL DATA

	COMPOSITION	Transparent satin film
	THICKNESS	85 µm
	SIZE	A3/A4

APPLICATION INSTRUCTIONS

	TEXTILE	Cotton Polyester Acrylic & similar fibres
	TIME & TEMPERATURE	160°C - 320°F / 20s
	PRESSURE	Medium
	PEEL	Cold

PRODUCT HIGHLIGHTS

- A heat transfer film specially developed for use with office printers (inkjet printers).
- Inks dry quickly → Saves time.
- Good opacity.
- Matt finish
- Soft to the touch.
- Very comfortable to wear, thanks to its thinness.

CARE & MAINTENANCE

- Always respect the garment instructions.
- Wash inside out to extend the design's life.
- Allow 24 hours after application before first wash.
- Avoid the use of aggressive products.
- Do not bleach.

STEP BY STEP : HOW TO USE

STEP 1 - PRINTING AND CUTTING

Program the printing and cutting of the design without rotating using a mirror mode. Define the we recommend that you cut this product cut this product by hand.

Step 2 - Trimming

Remove excess material (easy weeding).


Step 3 - Application

Position the visual on the textile and press with a Sefa DUPLEX/ROTEX press or equivalent, at 160°C/320°F for 20 seconds, using medium medium pressure.

We recommend the use of silicone paper to protect the visuals and the textile during during application.

Step 4 - Peeling

Cold peel.

Washing	Ironing	Tumble-dry
 40°C / 104°F	 Reverse side	 Authorized

STORAGE

- Storage life recommendation is up to one year.
- Store product in dry room with 15°-30°C/ 60°-85°F.
- Keep away from sunlight, store in a vertical position.

NOTE: We highly recommend that you perform tests before production.