Chemica
HEAT TRANSFERS FOR TEXTILES

WINPRINT

OUR COST-EFFECTIVE PRINTABLE MEDIA WITH A BRIGHT FINISH !

Our new **WINPRINT** is a PU printable media that you will be able to use on any kind of textile (cotton, polyester, acrylic, polycotton). It will allow you to succeed with all kind of designs while limiting your costs!

TECHNICAL SPECIFICATIONS

COMPOSITION	Polyurethane
THICKNESS	110 µm
CARRIER	PET
COMPATIBLE INKS	Solvent - eco-solvent inks
CUTTING	Flex blade 45°
CERTIFICATIONS	REACH
APPLICATIONS	Cotton, polyester, acrylic, polycotton
TEMPERATURE	140°C/ 284°F - 20 s
PRESSURE	Medium
PEELING	Hot
RECOMMANDED TAPE	ATT490

PRODUCT HIGHLIGHTS

- Good printable quality.
- White aspect, very soft touch.
- Easy to cut and easy to weed.
- This printable media offers very nice results and allows an optimal durability of your prints.

CARE & MAINTENANCE

- Always respect the garment instructions.
- Follow the instructions provided by the printer manufacturer and take care of the printing and drying temperatures (40°C/104°F)
- Avoid the use of non official inks from the printer manufacturer.
- Avoid the use of aggressive products.
- Wash inside out to extend the design's life.
- Allow 24 hours after application before first wash.
- Do not bleach.

Washing	Ironing	Tumble-dry	Dry-clean
40°C / 104°F	Reverse side	No	No

STORAGE

- Storage life recommendation is up to one year.
- Store product in dry room with 15°-30°C / 59°-86°F.
- Keep away from sunlight in a vertical position.

STEP BY STEP : HOW TO USE YOUR PRODUCT

STEP 1 - Cut design without mirroring & define the cut marks.

STEP 2 - Weed the excess easily.

STEP 3 - Wait a min. of 4 hours before applying the tape to allow proper inks drying.

STEP 4 - Apply design on garment.

STEP 5 - Press and peel warm.

NOTE: We highly recommend that you perform tests of printing, cutting and application before production.

FLEXDEV GROUP
TRANSFER YOUR IMAGINATION