



FIRSTMARK

THE ECO-FRIENDLY AND COST-EFFECTIVE HEAT TRANSFER VINYL.

This high-quality PVC heat transfer vinyl is easy to cut, easy to weed and easy to apply. It is also phthalate-free.

TECHNICAL DATA

	COMPOSITION	VINYL
	THICKNESS	110 µm
	CARRIER	Transparent adhesive polyester carrier

CUT SETTINGS

	SIDE	Mirror cut
	CUTTING	45° flex blade

APPLICATION

	TEXTILE	Cotton, polyester, polycotton
	TIME & TEMPERATURE	120°C- 248°F / 20s
	PRESSURE	Medium
	PEEL	Cold peel

CERTIFICATIONS



STANDARD
100
CQ 909/2
IFTH

www.oeko-tex.com

Yes all colours



Yes



Yes

PRODUCT HIGHLIGHTS

- Phthalate-free vinyl.
- Soft feel with a semi-gloss finish.
- Ideal for workwear, promotional wear, sportswear and fashion apparel.
- Easy to cut and weed.
- High-temperature washable and abrasion resistant.

CARE & MAINTENANCE

- Always follow the care instructions for the garment.
- Wash inside out to extend the design's life.
- Wait 24 hours after application for the first wash.
- Avoid using of aggressive products.
- Do not bleach.

WASHING



60°C / 140°F

IRONING



Inside out only

TUMBLE-DRY



Allowed

STEP BY STEP : HOW TO USE

STEP 1 - Perform a test cut using your cutting plotter.

STEP 2 - Mirror cut the heat transfer vinyl using a 45° flex blade.

STEP 3 - Weed the excess material and apply the design to the garment.

STEP 4 - Press and cold peel the carrier.

STORAGE

- Storage life recommendation is maximum one year.
- Store product in dry room at 15°-30°C/ 60°-85°F.
- Keep away from sunlight, store in a vertical position.

NOTE: We strongly recommend carrying out cutting, heat press and application tests before production.

CHEMICA SAS  35 rue de Malacussy , 42000 Saint-Etienne, FRANCE