



HOTMARK REVOLUTION

UNLIMITED CREATIVE POSSIBILITIES.

Optimized features for fast application at low temperature, compatible with all types of fabrics.

TECHNICAL DATA

	COMPOSITION	PU
	THICKNESS	75 µm
	CARRIER	Transparent adhesive polyester carrier

CUT SETTINGS

	SIDE	Mirror cut
	CUTTING	45° flex blade

APPLICATION

	TEXTILE	Cotton, polyester, polycotton, nylon fabrics
	TIME & TEMPERATURE	Quick application : 140°C/284°F - 5s Low temp. : 120°C/248°F - 20s Nylon : 1° step: 140°C/284°F - 5s / 2° step: 140°C/284°F - 15s
	PRESSURE	Medium
	PEEL	Cold peel or Hot peel

CERTIFICATIONS



STANDARD
100
CQ 909/2
IFTH

www.oeko-tex.com



Excluding fluorescent colours Yes

Yes

PRODUCT HIGHLIGHTS

- Universal heat transfer vinyl suitable for a wide range of fabrics.
- Multiple application options.
- Semi-matte finish.
- Available in 41 colours.
- Hot or cold peel.

CARE & MAINTENANCE

- Always follow the care instructions for the garment.
- Wash inside out to extend the design's life.
- Wait 24 hours after application for the first wash.
- Avoid using of aggressive products.
- Do not bleach.

WASHING



60°C / 140°F
40°C / 104°F

IRONING



Inside out only

TUMBLE-DRY



Allowed

STEP BY STEP : HOW TO USE

STEP 1 - Perform a test cut using your cutting plotter.

STEP 2 - Mirror cut the heat transfer vinyl using a 45° flex blade.

STEP 3 - Weed the excess material and apply the design to the garment.

STEP 4 - Press and peel the carrier hot or cold.

STORAGE

- Storage life recommendation is maximum one year.
- Store product in dry room at 15°-30°C/ 60°-85°F.
- Keep away from sunlight, store in a vertical position.

NOTE: We strongly recommend carrying out cutting, heat press and application tests before production.

CHEMICA SAS 35 rue de Malacussy , 42000 Saint-Etienne, FRANCE