

## BLING-BLING STAR™

### THE MOST SPARKLING HEAT TRANSFER FILM FOR TRENDY PERSONALISATIONS

Looking for a qualitative heat transfer film fully in line with latest fashion trends? Bling Bling is the best sparkling flex for fashion garments and soft accessories personalisation, also offering an overlapping feature for even more applications.

#### Fashion garment and accessories



#### Baby and kids



#### Product description


- ✓ Glittering is present everywhere on Fashion weeks and currently drives fashion trends! Add it now to your range.
- ✓ Discover our 12 colours:



Star  
Gold  
1121



Star  
Orange  
1127




Star  
Red  
1123



Star  
Pink  
1126



Star Dark  
Purple  
1136



Star  
Green  
1125



Star Light  
Blue  
1124



Star Navy  
Blue  
1132



Star  
Multi  
1135



Star Black  
Gold  
1134



Star  
Silver  
1120



Star  
Black  
1128


#### Application key points

- ✓ Great 3D glittering texture & finish.
- ✓ OEKO TEX Standard 100 class I certified, allowing application even on baby & kids clothing.
- ✓ Qualitative sparkling product without any glitter flakes shedding.

#### Usage benefits

- ✓ Overlapping features. No marks when repressed.
- ✓ Can be peeled hot or cold for more flexibility in your process.
- ✓ Clean finish, with no glue excess.
- ✓ Great to give more life to your trendiest designs.

SPECIFICATIONS

Composition	Average Thickness	Carrier	Dimensions	Certifications
Polyester Aluminium	350 µm	Adhesive & Transparent Polyester	50 cm x 25 m 50cm x 5 m 30 cm x 20 m	 All references: Class I

APPLICATION INSTRUCTIONS

Applies on	Cutting	Application Temp. & Duration
Cotton Polyester Acrylic & similar fibers	Use a Flock Blade 60°	160°C – 20 s 320°F – 20 s

Pressure	Peeling
Medium	Hot or Cold

Step 1 – Cutting

Set up the cutting of your heat transfer film in mirror mode and use a standard flock blade (60°).

Step 2 – Weeding

Remove the excess of material (easy weeding).

Step 3 – Application

Position your design on the textile and press it with a Sefa DUPLEX/ROTEX or equivalent at 160°C/320°F for 20 seconds.

We do recommend the use of a silicone paper to protect the designs and the textile during the application.

Step 4 – Peeling

Peel the material while hot or cold.

NOTE: We highly recommend you to perform tests before launching a production.

CARE AND MAINTENANCE RECOMMENDATIONS

Washing	Ironing	Tumble-dry	Dry cleaning
Up to 40°C/104°F	On reverse side only	Not recommen- ded	Not recommen- ded
Storage life	Storage Temperature & Lightning		Position
Up to 1 year	Dry room with 15°C-30°C/ 59°F-86°F	Away from sunlight	Vertical

Care and maintenance:

- ✓ Always respect the garments' instructions.
- ✓ Wait 24 hours after the application before the first wash.
- ✓ Avoid the use of aggressive products.

Washing recommendations:

- ✓ Respect the textile recommendations.
- ✓ Preferably inside out to extend the design's life.
- ✓ Do not bleach.