




ATT 450 TM - Ref. 5450

THE MEDIUM TACK AND MULTI-PURPOSE TAPE

Looking for a medium tacking tape with a white cellular backing film? This application tape ATT 450 is the most adapted transfer tape to all kind of product without damaging the design finish.



PRODUCT APPLICATION

| PRODUCTS | ATT 490 | ATT 500 | ATT 450 Medium tack with backing | ATT 600 |
|-------------------------|------------|----------|--|------------|
| POLYURETHANE | | | | |
| HOTMARKPRINT REVOLUTION | | | ✓ | |
| HOTMARKPRINT | √ | ✓ | ✓ | |
| HOTMARKPRINT SIR | ✓ | √ | ✓ | |
| HOTMARKPRINT NYLON | √ | ✓ | ✓ | |
| FIFTYPRINT | √ | | ✓ | |
| SPECIAL EFFECTS | | | | |
| GLITTERPRINT | | | | ✓ |
| METALPRINT | | ✓ | | |
| VINYL | | | | |
| EASYPRINT | ✓ | ✓ | ✓ | |
| EASYPRINT SIR | ✓ | ✓ | ✓ | |
| EASYPRINT NYLON | √ | ✓ | ✓ | |
| APRINT | | | ✓ | |
| SUNMARKPRINT | | | ✓ | |
| FLOCK | | | | |
| FLOKPRINT | | | ✓ | |

Product description

- ✓ Medium tack → doesn't damage the product during the transfer.
- ✓ Easy to use → adapted to almost all Chemica's printable transfer media.
- ✓ Recommended for small and big designs, even very small details.

SPECIFICATIONS

| Tack | Average Thickness | Composition | Dimension | Storage temperature |
|--------------|-------------------|--|------------|--------------------------------------|
| Medium ++ | 100 μm | Adhesive & Transparent Polyester | 50cm x 25m | Dry room with 15°C-30°C/59°F-86°F |