

ATT 600™ — Ref. 5600

THE HIGHEST TACK OF TAPE OF THE MARKET

Looking for a very powerful tape? This application tape ATT 600 is a very resistant tape and it doesn't allow bubbles air appearance. Thanks to its smooth backing, this tape is perfect to stock printed logos and designs.



Product description

- ✓ High tack → Perfect for very small designs and very easy to peel.
- ✓ Smooth backing → Great for stocking design and is not going to affect the design finish.
- ✓ Doesn't let air bubbles.
- ✓ Recommended for thick products and complex designs.

PRODUCT APPLICATION

| PRODUCTS | ATT 490 | ATT 500 | ATT 450 | ATT 600 High tack With backing |
|-------------------------|---------|---------|---------|--------------------------------------|
| POLYURETHANE | | | | |
| HOTMARKPRINT REVOLUTION | | | ✓ | |
| HOTMARKPRINT | ✓ | ✓ | ✓ | |
| HOTMARKPRINT SIR | ✓ | ✓ | ✓ | |
| HOTMARKPRINT NYLON | ✓ | ✓ | ✓ | |
| FIFTYPRINT | ✓ | | ✓ | |
| SPECIAL EFFECTS | | | | |
| GLITTERPRINT | | | | ✓ |
| METALPRINT | | ✓ | | |
| VINYL | | | | |
| EASYPRINT | ✓ | ✓ | ✓ | |
| EASYPRINT SIR | ✓ | ✓ | ✓ | |
| EASYPRINT NYLON | ✓ | ✓ | ✓ | |
| APRINT | | | ✓ | |
| SUNMARKPRINT | | | ✓ | |
| FLOCK | | | | |
| FLOKPRINT | | | ✓ | |

SPECIFICATIONS

| Tack | Average Thickness | Composition | Dimension | Storage temperature |
|-------------|-------------------|----------------------------------------|-------------|--------------------------------------|
| High +++ | 170 µm | Adhesive & Transparent Polyester | 100cm x 10m | Dry room with 15°C-30°C/59°F-86°F |