



ALLJET DARK 803



SATINY
FILM



160°C



PEEL : COLD



Flex Blade 45°
Medium pressure



105-110 μm



20 Sec

SPECIFICATIONS

APPLICATION

1. Printing and cutting

- Print the image on positive
- Cut the design with a plotter and weed the excess material

2. Heat pressing

- Transfer the image by hand.
- Position and heat press on a SEFA machine the image on the garment protected by a silicone paper at 160°C – 20 seconds – medium pressure.

THICKNESS:



White satiny film 105-110 microns
For use on inkjet and eco solvent printers.

CARRIER: Paper



APPLIES ON

This product is recommended for dark fabrics.

Cotton ● Polyester ● Acrylic and similar fibres.

CARE & MAINTENANCE

- Always respect the garment's instructions
- Allow 24 hours after application before washing
- Iron the backside only
- Printable media are very sensitive: always handle with care and preferably with gloves.
- Always store the roll in a plastic bag protected from dust.
- It is important always using official inks from the printer manufacturer.

WASH

- Max 40°C
- Preferably inside out
- Do not bleach
- Tumble-dry unapproved
- Dry-cleaning unapproved

STORE

- Up to 1 year
- In a dry room (15-25°C)
- Away from sunlight
- In vertical position

Chemica
Heat transfers for textiles

NOTE: For best results, it is recommended to TEST prior to starting standard production