







POLYURETHANE



75 µm



Z Medium to high Pressure

3	Low Temperature	Quick application
$\odot$	150°C	140°C
<b>→</b> °(	<b>20</b> s	<b>5</b> s



## NYLON




POLYURETHANE





Flex blade







## **SPECIFICATIONS**

# **APPLICATION**

- 1. Cut the material in reverse with a Flex regular blade.
- 2. Weed the excess material.
- 3. Heat press using a SEFA machine on the garment following instructions (time and temperature) & Protect the polyester carrier with silicone paper.
  - 4. Peel the carrier off when cold or hot.



**THICKNESS: 75 microns** 

**CARRIER: Adhesive & Transparent polyester** 

CERTIFICATES: Oeko-Tex Label Standard 100 Class I

Oeko-Tex Label Standard 100 Class 2



Cotton • Polyester • Acrylic • Similar Fibres Nylon

- Always respect the garment's instructions
- Allow 24 hours after application before washing
- Iron the backside only

### **WASH**

- Max 60°C : Cotton & Polyester Max 40°C: Nylon
- Preferably inside out
- Do not bleach
- **Tumble-dry approved**
- **Dry-cleaning approved**

### **STORE**

- Up to 1 year
- In a dry room (15-30° C)
- Away from sunlight
- In vertical position

