



NEWJET** - Ref. 804

THE GLOSSY PRINTABLE MEDIA DEDICATED TO PERSONALISATION OF LIGHT COLOURED TEXTILES

Looking to personalise textile supports with a homedesk inkjet printer? Newjet is a printable media with a glossy finish and soft touch fully compatible with homedesk printers and it is dedicated for light coloured textile.

Fashion Accessories



Product description

- ✓ Specially developed for home desk printers (inkjet printers).
- ✓ Fast drying inks process → saves production time.
- ✓ Good opacity.
- ✓ Glossy finish with an extra transparent effect.
- ✓ Soft-touch.
- ✓ Very comfortable to wear, thanks its thinness.

Application key points

- \checkmark No tape needed for application → saves money.
- ✓ The designs are directly printed on the product.
- ✓ Also compatible with solvent and eco-solvent inks.
- ✓ Easy to cut thanks its thinness.
- ✓ Specially for medium designs and logos.

Usage benefits

- ✓ Specially suitable for light coloured textiles.
- ✓ Recommended for home deco and fashion accessories.



SPECIFICATIONS

Average Thickness	Composition	Dimensions	Inks compatibility
85μm	Clear satiny film	Available in: A3 A4 144cm × 20m 72cm × 20m	Eco-Solvent Inkjet Check our website for technical Advice

APPLICATION INSTRUCTIONS

Applies on	Cutting	
Light coloured textiles such as Cotton Polyester	160°C – 20 s 320°F – 20 s	
Acrylic and similar fibers		

Pressure	Peeling	Recommended Transfer
Medium	Cold	By Hand

Step 1 - Print & Cut

Program the printing and cutting of the design without rotating the images and define the cut marks.

Step 2 - Weeding

Remove the excess material (easy weeding).

Step 3 – Application

Pre-press the textile for about 5 seconds to flatten it and release any excess moisture.

Position your design on the textile and press it with a Sefa DUPLEX/ROTEX or equivalent at $160^{\circ}\text{C}/320^{\circ}\text{F}$ for 20 seconds with a medium pressure.

We do recommend the use of a silicone paper to protect the designs and the textile during application.

Step 4 - Peeling

If a Tape was used, peel when cold.

NOTE: We highly recommend you to perform tests before launching a production.

CARE AND MAINTENANCE RECOMMENDATIONS

Washing	Ironing	Tumble- dry	Dry cleaning
Up to 40°C/104°F	On reverse side only	Yes	Not recommen- ded

Storage life	Storage Temperature	Storage Lighting	Position
Up to 1 year	Dry room with 15°C-30°C/ 59°F-86°F	Away from sunlight	Vertical position

Care and maintenance:

- ✓ Respect the garments' instructions.
- ✓ Follow the instructions provided by the printer manufacturer.
- ✓ It is important to always use official inks from the printer manufacturer.
- ✓ Printable media are very sensitive: always handle with care and preferably with gloves.
- ✓ Wait 24 hours before the first wash.
- ✓ Avoid the use of aggressive products.

Washing recommandations:

- ✓ Preferably inside out to extend design life.
- ✓ Do not bleach.