



BLING-BLING™

THE MOST SPARKLING HEAT TRANSFER FILM FOR TRENDY PERSONALISATIONS

Looking for a qualitative heat transfer film fully in line with latest fashion trends? Bling Bling is the best sparkling flex for fashion garments and soft accessories personalisation, also offering an overlapping feature for even more applications.

Fashion garment and accessories



Baby and kids



Product description

- ✓ Glittering is present everywhere on Fashion weeks and currently drives fashion trends! Add it now to your range.
- ✓ Discover our 12 colours:



Application key points

- ✓ Great 3D glittering texture & finish.
- ✓ OEKO TEX Standard 100 class I certified, allowing application even on baby & kids clothing.
- Qualitative sparkling product without any glitter flakes shedding.

Usage benefits

- ✓ Overlapping features. No marks when repressed.
- Can be peeled hot or cold for more flexibility in your process.
- ✓ Clean finish, with no glue excess.
- ✓ Great to give more life to your trendiest



SPECIFICATIONS

Composition	Average Thickness	Carrier	Dimensions	Certifications
Polyester Aluminium	350 μm	Adhesive & Transparent Polyester	50 cm x 25 m 50cm x 5 m 30 cm x 20 m	STANDARD 100 #

APPLICATION INSTRUCTIONS

Applies on	Cutting	Application Temp. & Duration
Cotton Polyester Acrylic & similar fibers	Use a Flock Blade 60°	160°C - 20 s 320°F - 20 s

Pressure	Peeling	
Medium	Hot or Cold	

Step 1 - Cutting

Set up the cutting of your heat transfer film in mirror mode and use a standard flock blade (60°).

Step 2 - Weeding

Remove the excess of material (easy weeding).

Step 3 - Application

Position your design on the textile and press it with a Sefa DUPLEX/ROTEX or equivalent at 160°C/320°F for 20 seconds.

We do recommend the use of a silicone paper to protect the designs and the textile during the application.

Step 4 - Peeling

Peel the material while hot or cold.

NOTE: We highly recommend you to perform tests before launching a production.

CARE AND MAINTENANCE

15°C-30°C/

59°F-86°F

vear

DECOMMENDATIONS								
	Washing		Ironing	Tumble- dry	Dry cleaning			
	Up to 40°C/104°F		On reverse side only	Not recommen- ded	Not recommen- ded			
	Storage life	S	torage Tem Lightr	Position				
	Up to 1	Dr	y room with	Away	Vertical			

from

sunlight

Care and maintenance:

- ✓ Always respect the garments' instructions.
- ✓ Wait 24 hours after the application before the first wash.
- ✓ Avoid the use of aggressive products.

Washing recommendations:

- ✓ Respect the textile recommendations.
- ✓ Preferably inside out to extend the design's life.
- ✓ Do not bleach.