

SUBLIFLOK™ – Ref. 1602

THE VELVET TOUCH PRINTABLE MEDIA FOR SUBLIMATION PRINTING

Looking for a sublimation media with a special touch personalisation? Subliflok is a smooth touch sublimation printable media developed specially to be printed directly with sublimation inks only.

Fashion Accessories



Home Decor



Product description

- ✓ Specially developed to absorb sublimation inks directly from the impression.
- ✓ Smooth velvet touch.
- ✓ Suede-like finish.
- ✓ Very resistant to washing at high temperatures.

Application key points

- ✓ Perfect for medium designs such as names and number.
- ✓ Printed directly on the product → no need of sublimation paper to transfer the inks.
- ✓ No tape required → saves production time.

Usage benefits

- ✓ Recommended for home decor and fashion accessories.

SPECIFICATIONS

| Composition | Carrier | Dimensions | Inks compatibility |
|-------------|--|---------------------------|--------------------|
| Fibers | White polyester flock media (velvet touch) | Available in 50 cm x 10 m | Sublimation |

APPLICATION INSTRUCTIONS

| Applies on | Cutting | Application Temp. & Duration |
|---|-----------------------|------------------------------|
| Cotton Polyester Acrylic & similar fibres | Flock Blade of 60° | 170°C – 50 s 338°F – 50 s |

Recommended tape

No tape

Step 1 – Print & Cut :

Program the printing and cutting of the design without rotating the image. Define the cut marks.

Step 4 – Application on textile :

Remove the backing carrier, place your design on the textile and protect it with a silicone paper. Press it with a Sefa DUPLEX/ROTEX or equivalent at 170°C/338°F during 50 seconds.

For sensitive garments:

1st- Heat press the logo at 170° /338°F during 50 seconds with the backing carrier

2nd- Remove the backing carrier and heat press again the logo, on the garment this time at 160°C /320°F during 20 seconds.

NOTE: We highly recommend you to perform tests before launching a production.

CARE AND MAINTENANCE RECOMMENDATIONS

| Washing | Ironing | Tumble-dry | Dry cleaning |
|--------------------------------|----------------------|-----------------|-----------------|
| Up to 60°C/140°F Inside out | On reverse side only | Not recommended | Not recommended |

| Storage life | Storage Temperature | Storage Lighting | Position |
|--------------|---------------------------------------|--------------------|-------------------|
| Up to 1 year | Dry room with 15°C-30°C/ 59°F-86°F | Away from sunlight | Vertical position |

Care and maintenance:

- ✓ Respect the garments’ instructions.
- ✓ Follow the instructions provided by the printer manufacturer and take care of the printing (40°C/104°F) and drying temperature (45°C/113°F).
- ✓ It is important to always use official inks from the printer manufacturer.
- ✓ Printable media are very sensitive: always handle with care and preferably with gloves.
- ✓ Wait 24 hours before the first wash.
- ✓ Avoid the use of aggressive products.

Washing recommendations:

- ✓ Preferably inside out to extend design life.
- ✓ Do not bleach.