

# 1810 NEWLASER

OEKO-TEX®  
CONFIDENCE IN TEXTILES  
STANDARD 100 

Class 1

 PAPER	 7 mil	 No Blade	 FIRM pressure	 360°F 360°F	 30s 30s	 PEEL: COLD
--	--	--	---	--	---	---

CARRIER: Paper

**APPLIES ON**  
 Light Colored  
Cotton Only

**CARE**

- Always respect the garment's instructions
- Allow 24 hours after application before washing
- Iron the backside only

**WASH**

- Max 85°F
- Preferably inside out
- Do NOT bleach
- Do NOT tumble-dry
- Do NOT Dry-clean

**STORE**

- Up to 1 year
- In a dry room (60-75°F)
- Away from sunlight
- In a plastic bag protected from dust

## APPLICATION

1. Print your design in reverse (mirror) and use the printer setting for Label 1. NOTE: It is recommended to use OEM printer inks. For best results, we recommend the use of a white toner laser printer. Printable medias are very sensitive: always handle with care, preferably with gloves.
2. Preheat the lower platen of your heat press by closing it for a few seconds. Position and heat press your logo on the garment protected by 1813 Cover Sheet at 360°F–30 seconds – firm pressure.
3. Wait 5-10 seconds before peeling the backing off the textile, while still on the heat press.
4. Press your logo again protected by 1813 Cover Sheet at 360°F–30 seconds – firm pressure. Remove when cold. This will set the inks and leave you with a matte finish.

 **hemica US**  
Transfer your imagination

NOTE: For best results, we recommend performing a TEST prior to starting standard production